

LISTING OF THE CLAIMS

What is claimed, is:

1. (currently amended) A method of monitoring events in a computer network, the method comprising:

said computer network triggering said events, each event being provided with attribute values allocated to a given set of attributes of said each event,

simultaneously monitoring various event attributes from said given set of attributes versus the arrival time of said each event ~~the events~~,

providing an event display with a cross plot having x and y coordinate axes, the x-axis presenting a time period and the y-axis presenting an attribute value range, and visualizing data along said x and y coordinate axes, said axes being attribute axes,

determining a primary attribute of said each event ~~the events~~ selected from the given set of attributes to be presented with its attribute values on the y-axis of the cross plot,

allocating a first display label to the events indicating the attribute values of the primary attribute, providing a pattern algorithm to detect whether an arrived event is part of the given pattern on the basis of a comparison of the attributes allocated to the given pattern and of the attributes assigned to the arrived event, providing a mapping algorithm to map any attribute value of an attribute selected from the given set of attributes onto the y-axis of the cross plot,

allocating a second display label to said each event ~~the events~~ indicating the attribute values of the attributes being uncovered as part of the given pattern,

1 plotting all the events that arrived within the time period and including an attribute value
2 allocated to the primary attribute into the cross plot with the first display label indicating the
3 primary attribute, the position of the first display label of said each event in the cross plot being
4 determined on the basis of the attribute value of the primary attribute of the event and its arrival
5 time,

6
7 plotting the all events that arrived within the time period and being detected by means of the
8 pattern algorithm as part of the given pattern into the cross plot with the second display label
9 indicating the given pattern, the position of the second display label of said each event in the
10 cross plot being determined by the mapping algorithm on the basis of the attribute value of the
11 attribute of the event being uncovered as part of the given pattern and its arrival time, ~~and~~

12
13 viewing a secondary attribute of said each event together with the primary attribute on said
14 display; and

15
16 automatically generating a large variety of visualizations along other attribute axes, and
17 identifying correlations by superimposing and cross-referencing these visualizations.

18
19 2. (original) The method according to claim 1, further comprising:

20
21 recording the attribute values and the arrival time of a new event, determining on the basis of the
22 recorded attribute values of event whether or not the newly arrived event includes an attribute
23 value of the primary attribute, and if the newly arrived event includes the attribute value for the
24 primary attribute shifting the x-axis of the cross plot so that the time period being presented on
25 the x-axis covers the arrival time of the event, and

26
27 plotting the event arrived within the shifted time period into the cross plot with the first display
28 label indicating the primary attribute.

29
30 3. (original) The method according to claim 2 comprising the further steps of:

1 determining on the basis of the recorded attribute values of event whether or not the newly
2 arrived event is part of the given pattern on the basis of a comparison of the attributes allocated
3 to the given pattern and of the attributes assigned to the arrived event,
4
5 if the newly arrived event includes an attribute value of the given pattern adding the event to the
6 previous events being detected as part of the given pattern, and
7
8 redrawing all the events being associated with given pattern in the cross plot.

9
10 4. (currently amended) The method according to claim 3, further comprising:
11

12 if the newly arrived event does not include an attribute value of the given pattern, determining on
13 the basis of the recorded attribute values of all previous arrived events by means of the pattern
14 algorithm whether or not the newly arrived event is part of a new pattern on the basis of a
15 comparison of the attributes allocated to the new pattern and of the attributes assigned to the
16 arrived events;

17
18 if the newly arrived event forms together with previous recorded events the new pattern,
19 allocating a third display label to the events indicating the attribute values of the attributes being
20 uncovered as part of the new pattern; and
21

22 plotting the all events being detected by means of the pattern algorithm as part of the new pattern
23 into the cross plot with the third display label indicating the new pattern, the position of the third
24 display label of said each event in the cross plot being determined by the mapping algorithm on
25 the basis of the attribute value of the attribute of the event being uncovered as part of the new
26 pattern and its arrival time.

27
28 5. (currently amended) The method according to claim 1, further comprising:
29

30 removing all the events including an attribute value allocated to the primary attribute from the
31 cross plot, if a primary attribute to be presented with its attribute values on the y-axis of the cross

1 plot is changed, allocating a fourth display label to the events indicating the attribute values of
2 the new primary attribute, and
3
4 plotting all the events arrived within the time period and including an attribute value allocated to
5 the new primary attribute into the cross plot with the fourth display label indicating the new
6 primary attribute, the position of the fourth display label of said each event in the cross plot
7 being determined on the basis of the attribute value of the primary attribute of the event and its
8 arrival time.

9
10 6. (original) The method according to claim 1 comprising the further steps of plotting all
11 attribute values recorded for an event with the respective display label into the cross plot if the
12 event is selected by an operator, and displaying textual information associated with the selected
13 event on the event display.

14
15 7. (original) The method according to claim 1, wherein the pattern algorithm is suitable to
16 perform multi-attribute pattern recognition.

17
18 8. (original) The method according to claim 1, wherein each display label includes a specific
19 color and/or a specific mark layout.

20
21 9. (original) The method according to claim 1, wherein all events being uncovered as part of the
22 pattern are clustered by the corresponding display label.

23
24 10. (currently amended) A method according to claim 1, further comprising employing a
25 computer readable program on tangible computer media containing comprising a
26 program code to cause the carrying carry out the steps of triggering, monitoring,
27 providing, determining, allocating a first display label, allocating a second display label,
28 plotting events including an attribute value, plotting events detected, viewing, and
29 automatically generating, the method of claim 1; when the program code is running on a
30 computer.

11. (currently amended) A computer program on a computer readable medium containing a program code to carry out the all steps of the method of claim 1, said program code being stored on data carrier.

12. (original) An event visualization device for monitoring events in a computer network, the device comprising means to perform ~~the~~ all steps of the method as claimed in claim 1.

13. (currently amended) An article of manufacture comprising a computer ~~usable~~ readable medium having computer readable program code means embodied therein for causing monitoring of events in a computer network, the computer readable program code means in said article of manufacture comprising computer readable program code means for causing a computer to effect ~~the~~ all steps of claim 1.

14. (currently amended) A program storage device being a computer readable medium by-machine, tangibly embodying a program of instructions executable by the machine to perform method steps for monitoring events in a computer network, said method steps comprising the steps of said computer network triggering said events, each event being provided with attribute values allocated to a given set of attributes of said each event, simultaneously monitoring various event attributes from said given set of attributes versus the arrival time of said each event ~~the events~~,

providing an event display with a cross plot having x and y coordinate axes, the x-axis presenting a time period and the y-axis presenting an attribute value range, and visualizing data along said x and y coordinate axes, said axes being attribute axes,

determining a primary attribute of said each event ~~the events~~ selected from the given set of attributes to be presented with its attribute values on the y-axis of the cross plot,

allocating a first display label to the events indicating the attribute values of the primary attribute, providing a pattern algorithm to detect whether an arrived event is part of the given pattern on the basis of a comparison of the attributes allocated to the given pattern and of the

1 attributes assigned to the arrived event, providing a mapping algorithm to map any attribute
2 value of an attribute selected from the given set of attributes onto the y-axis of the cross plot,
3
4 allocating a second display label to said each event ~~the events~~ indicating the attribute values of
5 the attributes being uncovered as part of the given pattern,
6
7 plotting all ~~the events~~ that arrived within the time period and including an attribute value
8 allocated to the primary attribute into the cross plot with the first display label indicating the
9 primary attribute, the position of the first display label of said each event in the cross plot being
10 determined on the basis of the attribute value of the primary attribute of the event and its arrival
11 time,
12
13 plotting ~~the all events~~ that arrived within the time period and being detected by means of the
14 pattern algorithm as part of the given pattern into the cross plot with the second display label
15 indicating the given pattern, the position of the second display label of said each event in the
16 cross plot being determined by the mapping algorithm on the basis of the attribute value of the
17 attribute of the event being uncovered as part of the given pattern and its arrival time, ~~and~~
18
19 viewing a secondary attribute of said each event together with the primary attribute on said
20 display, and
21
22 automatically generating a large variety of visualizations along other attribute axes, and
23 identifying correlations by superimposing and cross-referencing these visualizations.
24

25 15. (currently amended) A computer program product comprising a computer ~~usable~~ readable
26 medium having computer readable program code means embodied therein for causing the event
27 visualization device, the computer readable program code means in said computer program
28 product comprising computer readable program code means for causing a computer to effect the
29 all functions of claim 12.
30

31 16. (previously presented) The method according to claim 1, further comprising:

1
2 recording the attribute values and the arrival time of a new event, determining on the basis of the
3 recorded attribute values of event whether or not the newly arrived event includes an attribute
4 value of the primary attribute, and if the newly arrived event includes the attribute value for the
5 primary attribute shifting the x-axis of the cross plot so that the time period being presented on
6 the x-axis covers the arrival time of the event,
7
8 plotting the event arrived within the shifted time period into the cross plot with the first display
9 label indicating the primary attribute;
10
11 determining on the basis of the recorded attribute values of event whether or not the newly
12 arrived event is part of the given pattern on the basis of a comparison of the attributes allocated
13 to the given pattern and of the attributes assigned to the arrived event;
14
15 if the newly arrived event includes an attribute value of the given pattern adding the event to the
16 previous events being detected as part of the given pattern;
17
18 redrawing all the events being associated with given pattern in the cross plot;
19
20 if the newly arrived event does not include an attribute value of the given pattern, determining on
21 the basis of the recorded attribute values of all previous arrived events by means of the pattern
22 algorithm whether or not the newly arrived event is part of a new pattern on the basis of a
23 comparison of the attributes allocated to the new pattern and of the attributes assigned to the
24 arrived events;
25
26 if the newly arrived event forms together with previous recorded events the new pattern,
27 allocating a third display label to the events indicating the attribute values of the attributes being
28 uncovered as part of the new pattern; and
29
30 plotting the all events being detected by means of the pattern algorithm as part of the new pattern
31 into the cross plot with the third display label indicating the new pattern, the position of the third

1 display label of each event in the cross plot being determined by the mapping algorithm on the
2 basis of the attribute value of the attribute of the event being uncovered as part of the new pattern
3 and its arrival time;

4
5 17. (previously presented) The method according to claim 16, further comprising:

6
7 removing all the events including an attribute value allocated to the primary attribute from the
8 cross plot, if a primary attribute to be presented with its attribute values on the y-axis of the cross
9 plot is changed, allocating a fourth display label to the events indicating the attribute values of
10 the new primary attribute, and

11
12 plotting all the events arrived within the time period and including an attribute value allocated to
13 the new primary attribute into the cross plot with the fourth display label indicating the new
14 primary attribute, the position of the fourth display label of each event in the cross plot being
15 determined on the basis of the attribute value of the primary attribute of the event and its arrival
16 time.

17
18 18. (previously presented) The event visualization device for monitoring events in a computer
19 network, according to claim 12, further comprising:

20
21 means for recording the attribute values and the arrival time of a new event, means for
22 determining on the basis of the recorded attribute values of event whether or not the newly
23 arrived event includes an attribute value of the primary attribute, and if the newly arrived event
24 includes the attribute value for the primary attribute shifting the x-axis of the cross plot so that
25 the time period being presented on the x-axis covers the arrival time of the event,

26
27 means for plotting the event arrived within the shifted time period into the cross plot with the
28 first display label indicating the primary attribute;

1 means for determining on the basis of the recorded attribute values of event whether or not the
2 newly arrived event is part of the given pattern on the basis of a comparison of the attributes
3 allocated to the given pattern and of the attributes assigned to the arrived event;

4
5 means for adding for if the newly arrived event includes an attribute value of the given pattern
6 adding the event to the previous events being detected as part of the given pattern;

7
8 means for redrawing all the events being associated with given pattern in the cross plot;

9
10 means for determining if the newly arrived event does not include an attribute value of the given
11 pattern, means for determining on the basis of the recorded attribute values of all previous
12 arrived events by means of the pattern algorithm whether or not the newly arrived event is part
13 of a new pattern on the basis of a comparison of the attributes allocated to the new pattern and of
14 the attributes assigned to the arrived events;

15
16 means for allocating if the newly arrived event forms together with previous recorded events the
17 new pattern, allocating a third display label to the events indicating the attribute values of the
18 attributes being uncovered as part of the new pattern; and

19
20 means for plotting the all events being detected by means of the pattern algorithm as part of the
21 new pattern into the cross plot with the third display label indicating the new pattern, the position
22 of the third display label of each event in the cross plot being determined by the mapping
23 algorithm on the basis of the attribute value of the attribute of the event being uncovered as part
24 of the new pattern and its arrival time;

25
26 19. (previously presented) The event visualization device for monitoring events in a computer
27 network, according to claim 18, further comprising:

28
29 means for removing all the events including an attribute value allocated to the primary attribute
30 from the cross plot, if a primary attribute to be presented with its attribute values on the y-axis of

1 the cross plot is changed, allocating a fourth display label to the events indicating the attribute
2 values of the new primary attribute, and
3
4 means for plotting all the events arrived within the time period and including an attribute value
5 allocated to the new primary attribute into the cross plot with the fourth display label indicating
6 the new primary attribute, the position of the fourth display label of each event in the cross plot
7 being determined on the basis of the attribute value of the primary attribute of the event and its
8 arrival time.
9

10 20. (currently amended) An article of manufacture comprising apparatus for monitoring events in
11 a computer network, the ~~method~~ apparatus comprising:

12
13 said computer network having means for triggering said events, each event being provided with
14 attribute values allocated to a given set of attributes of said each event,
15

16 means for simultaneously monitoring various event attributes from said given set of attributes
17 versus the arrival time of said each event ~~-the events~~,
18

19 means for providing an event display with a cross plot having x and y coordinate axes, the x-axis
20 presenting a time period and the y-axis presenting an attribute value range, and visualizing data
21 along said x and y coordinate axes, said axes being attribute axes,
22

23 means for determining a primary attribute of said each event ~~the events~~ selected from the given
24 set of attributes to be presented with its attribute values on the y-axis of the cross plot,
25

26 means for allocating a first display label to the events indicating the attribute values of the
27 primary attribute, providing a pattern algorithm to detect whether an arrived event is part of the
28 given pattern on the basis of a comparison of the attributes allocated to the given pattern and of
29 the attributes assigned to the arrived event, providing a mapping algorithm to map any attribute
30 value of an attribute selected from the given set of attributes onto the y-axis of the cross plot,
31

1 means for allocating a second display label to said each event ~~the events~~ indicating the attribute
2 values of the attributes being uncovered as part of the given pattern,

3
4 means for plotting ~~all the events~~ that arrived within the time period and including an attribute
5 value allocated to the primary attribute into the cross plot with the first display label indicating
6 the primary attribute, the position of the first display label of said each event in the cross plot
7 being determined on the basis of the attribute value of the primary attribute of the event and its
8 arrival time,

9
10 means for plotting ~~the all events~~ that arrived within the time period and being detected by means
11 of the pattern algorithm as part of the given pattern into the cross plot with the second display
12 label indicating the given pattern, the position of the second display label of said each event in
13 the cross plot being determined by the mapping algorithm on the basis of the attribute value of
14 the attribute of the event being uncovered as part of the given pattern and its arrival time, and

15
16 means for viewing a secondary attribute of said each event together with the primary attribute on
17 said display; and

18
19 means for automatically generating a large variety of visualizations along other attribute axes,
20 and identifying correlations by superimposing and cross-referencing these visualizations.